

## BCS Level 4 Award in Operating Systems Answer Key and Rationale – QAN 603/2894/0

Question	Answer	Explanation / Rationale	Syllabus Sections
1	A	Network Access Protocol allows administrators to disallow device access to the network if the device doesn't meet specific criteria such as update level, AV protection or a number of other conditions.	3.1
2	В	To disable a Windows service from the command line, the command sc config has to be used. It is also deliberate that there is no space between the '=' and 'start'. There must be a space between the '=' and 'disable'.	1.3
3	В	Active Directory group policies can be configured to force the download and installation of updates for Windows machines.	4.2
4	А	On all Apple IOS, this is the first step to entering the firewall configuration wizard.	1.1
5	А	DSAdd is a command line tool that allows an admin to add users, groups, computers and other objects to AD.	2.2
6	С	Inbound rules stipulate which ports are open on the local computer to allow access from external machines.	1.1
7	D	If a folder has had specific permissions set disallowing all but certain groups, any unauthorised user will be denied access.	2.3
8	В	Windows Server Update Services is what WSUS stands for and it is used with Windows.	4.1
9	С	If a mail client (such as Lotus Notes) has port 1352 blocked outbound, it will not be able to connect to the mail server.	1.2
10	В	Firewalls can be configured to deny and allow port access from untrusted and trusted sources / destinations.	4.2
11	С	Active Directory allows administrators to create security policies that can be deployed to users and computers. Active Directory is a technology whereas SCCM, Sites and Services and Policy editor are tools.	2.1
12	D	ADUC is Active Directory Users and Computers and is used to manage users and groups.	2.2
13	A	Software firewalls can prevent specific applications from accessing network ports, hardware firewalls are generally not able to do this.	1.4
14	В	All operating systems allow the creation of (file) shares to facilitate and control user access to files and folders.	3.2
15	В	FileVault will encrypt the startup disk of an Apple computer with a 256 bit key.	3.1
16	А	Firewalls protect computers and networks from unauthorised network access.	3.2
17	А	For OSX, sudo launchctl is the correct method to unload the service from the service start list.	1.3



Question	Answer	Explanation / Rationale	Syllabus Sections
18	С	Malware, such as keylogging software or other such data grabbing software, would utilise a specific open port or ports to send data to the command and control node.	1.2
19	D	Regedit.exe is the only valid answer. Reg.exe allows registry functions, but not a full management console.	2.1
20	В	Unused services or daemons can sometimes be listening on specific ports. If the service or daemon has a vulnerability, it gives hackers a potential attack vector to access the PC.	1.4